TOSHIBA

Ribbons for BA410/BA420

Product information

- The right ribbon quality for every application.
- Ribbons directly from the manufacturer: Toshiba original consumables are perfectly matched to Toshiba label printers and the used print head technologies. They guarantee high quality printing while also lowering abrasionof the print head.
- The perfect combination: Toshibas wide range of available ribbons is the outcome of years of research and development. Each of the ribbons offers different printing characteristics, which are specially adapted to the specific application.





ΔΤΙΟΝΙ



Protect your BA410/BA420 -With original ribbons from Toshiba



WAX qualities

Ideal use for storage, packaging, shipping, transport, logistics, and trade









AW1F

Wax Standard, competitive with good cost-performance ratio and suitable for a variety of materials

Cost	Durability	Surface		Width (mm
•0000	•0000	Standard	00000	60 mm
		Coated	•••00	76 mm
		Synthetic	00000	90 mm

Width (mm)	Length (m)	Article number
60 mm	400 m	BSA40060AW1F
76 mm	400 m	BSA40076AW1F
90 mm	400 m	BSA40090AW1F
110 mm	400 m	BSA40110AW1F

AW7F Wax Standard, solvent-free and suitable for most common paper materials

Cost	Durability	Surface		Width (mm)	Length (m)	Article numb
••000	00000	Standard	00000	60 mm	400 m	BSA40060AW
		Coated	00000	76 mm	400 m	BSA40076AW
		Synthetic	00000	90 mm	400 m	BSA40090AW
				110 mm	400 m	BSA40110AW7

AW6F Wax Premium, excellent print results at low temperatures and suitable for a variety of materials

Cost	Durability	Surface	
00000	••000	Standard	•••••
		Coated	
		Synthetic	0000

Width (mm)	Length (m)	Article number
60 mm	400 m	BSA40060AW6F
66 mm	400 m	BSA40066AW6F
76 mm	400 m	BSA40076AW6F
90 mm	400 m	BSA40090AW6F
110 mm	400 m	BSA40110AW6F

Article number BSA45060SW1 BSA45076SW1 BSA45088SW1 BSA45110SW1

SW1 Wax Premium, enhanced abrasion resistance due to higher resin content and suitable for a variety of materials

Cost	Durability	Surface		Width (mm)	Length (m)
00000	•••00	Standard	00000	60 mm	450 m
		Coated	•••••	76 mm	450 m
		Synthetic	•••00	88 mm	450 m
	-	0		110 mm	450 m

AG3

WAX-RESIN qualities





Ideal for use in distribution, retail, manufacturing, production and outdoor applications



Premium Wax-Resin, excellent print quality even with 90° rotated barcodes, very good abrasion resistance and suitable for matt-finished to semi-gloss materials

Cost	Durability	Surface	
•••00	•••00	Standard	•••••
		Coated	•••••
		Synthetic	

Width (mm)	Length (m)	Article number
60 mm	400 m	BSA40060AG3
66 mm	400 m	BSA40066AG3
76 mm	400 m	BSA40076AG3
82 mm	400 m	BSA40082AG3
90 mm	400 m	BSA40090AG3
99 mm	400 m	BSA40099AG3
110 mm	400 m	BSA40110AG3


SG1 Premium Wax-Resin, enhanced abrasion resistance and sharp dark print results and suitable for a variety of materials

Cost	Durability	Surface	
000	•••00	Standard	•••••
		Coated	•••••
		Synthetic	

Width (mm)	Length (m)	Article number
60 mm	450 m	BSA45060SG1
76 mm	450 m	BSA45076SG1
88 mm	450 m	BSA45088SG1
110 mm	450 m	BSA45110SG1

SG3 Premium Wax-Resin, excellent blackening and smudge resistance and suitable for papers and synthetics

Cost	Durability	Surface		Width (mm)	Length (m)	Article number
••000	•••00	Standard	00000	60 mm	450 m	BSA45060SG3F
		Coated		76 mm	450 m	BSA45076SG3F
		Synthetic	•••00	88 mm	450 m	BSA45088SG3F
	2	2		110 mm	450 m	BSA45110SG3F







AS1

RESIN qualities

Ideal for use in industrial, electronic, chemical, pharmaceutical, automotive and textile industry











Resin Standard, scratch- and heat resistant up to 180°C as well as conditionally solvent resistant and suitable for synthetic materials (PVC, PET, PE, PP)

Cost	Durability	Surface	
	•••••	Standard	0000
		Coated	$\bullet\bullet\bullet\circ\circ\circ$
		Synthetic	•••••

Width (mm)	Length (m)	Article number
60 mm	400 m	BSA40060AS1
66 mm	400 m	BSA40066AS1
76 mm	400 m	BSA40076AS1
82 mm	400 m	BSA40082AS1
90 mm	400 m	BSA40090AS1
99 mm	400 m	BSA40099AS1
110 mm	400 m	BSA40110AS1

SS3F Resin Standard, enhanced abrasion resistance and sharp dark print results and suitable for a variety of materials

Cost	Durability	Surface	
	•••••	Standard	0000
		Coated	•••00
		Synthetic	•••••

Width (mm)	Length (m)	Article number
60 mm	450 m	BSA45060SS3F
76 mm	450 m	BSA45076SS3F
88 mm	450 m	BSA45088SS3F
110 mm	450 m	BSA45110SS3F

AS2 Resin Premium, best heat resistance (250°C) and solvent resistance and suitable for synthetic materials (PVC, PET, PE, PP)

Cost	Durability	Surface		Width (mm)	Length (m)	Article number
00000	•••••	Standard	00000	60 mm	270 m	B4527060AS2
		Coated	00000	70 mm	270 m	B4527070AS2
		Synthetic	•••••	90 mm	270 m	B4527090AS2
				110 mm	270 m	B4527110AS2

Za več informacij se obrnite na nas:



UPRAVLJANJE STORITEV TISKANJA

TIFT, d.o.o., Kamniška 41, 1000 Ljubljana T: 01 600 10 20, M: 031 665 144, E: dobrodosli@tift.si, W: www.tift.si

Pridobili smo certifikat poslovne odličnosti: Excellent SME





Technical data is subject to change without prior notice. All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries. All rights reserved. We are constantly making efforts to deliver the latest status of data to our partners. Specifications for some models may change in the time between the production and the release of this documentation. Copyright © 2021 Toshiba Tec, ProductInformation_Ribbons for BA410/BA420_IDD_20210209